

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 15.07.2021

Version number 9 (replaces version 8)

Revision: 15.07.2021

SECTION 1: Identification of the substance/mixture and of the company undertaking

1.1 Product identifier

Trade name: **AMOTHERM WOOD 450 SB - A**

1.2 Relevant identified uses of the substance or mixture and uses advised against

Sector of Use

SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites

Product category PC9a Coatings and paints, thinners, paint removers

Process category

PROC11 Non industrial spraying

PROC10 Roller application or brushing

PROC7 Industrial spraying

Application of the substance / the mixture Antifire paint

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier:

J.F. AMONN srl div. Color

via cima i prà, 7

32014 Ponte nelle Alpi (BL)

ITALIA

Informing department:

Product safety department.

technical department Color Division

phone: +39 0437 98411

email: laboratorio@amonncolor.com

1.4 Emergency telephone number:

National Poisons Information Service (NPIS)

In England and Wales: NHS 111 - dial 111

In Scotland: NHS 24 - dial 111

In N Ireland: Contact your local GP or pharmacist during normal hours; click here (www.gpoutofhours.hscni.net/) for GP services Out-of-Hours.

In Republic of Ireland: 01 809 2166

Centro Antiveleni - Ospedale di Niguarda - Milano: +39 02 66101029

National Poisons Information Service

+44 121 507 4123

Members of the public seeking specific information on poisons should contact:

In England and Wales: NHS 111 - dial 111

In Scotland: NHS 24 - dial 111

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

Flam. Liq. 3 H226 Flammable liquid and vapour.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

Hazard pictograms



GHS02

Signal word Warning

Hazard statements

H226 Flammable liquid and vapour.

Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P240 Ground and bond container and receiving equipment.

P241 Use explosion-proof [electrical/ventilating/lighting] equipment.

(Contd. on page 2)

GB

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 15.07.2021

Version number 9 (replaces version 8)

Revision: 15.07.2021

Trade name: AMOTHERM WOOD 450 SB - A

(Contd. of page 1)

- P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.
- P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
- P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

- **2.3 Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

- **3.2 Mixtures**
- **Description:** Mixture of the substances listed below with nonhazardous additions.

- **Dangerous components:**

CAS: 123-86-4 EINECS: 204-658-1 Reg.nr.: 01-2119485493-29	n-butyl acetate Flam. Liq. 3, H226; STOT SE 3, H336, EUH066	10-25%
CAS: 13674-84-5 EINECS: 237-158-7 Reg.nr.: 01-2119486772-26-0005	Tris (2-chlorometiletil)phosphate Acute Tox. 4, H302	3-7%
CAS: 108-65-6 EINECS: 203-603-9 Reg.nr.: 01-2119475791-29	2-methoxy-1-methylethyl acetate Flam. Liq. 3, H226; STOT SE 3, H336	1.5-3%
Reg.nr.: 01-2119976378-19-0000	Fatty acids, sunflower-oil, conjugated, reaction products with maleic anhydride and tall-oil fatty acids Skin Irrit. 2, H315; Skin Sens. 1, H317	0.5-1.5%

- **Additional information** For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- **4.1 Description of first aid measures**
- **General information** Instantly remove any clothing soiled by the product.
- **After inhalation** Supply fresh air; consult doctor in case of symptoms.
- **After skin contact** The product is not skin irritating.
- **After eye contact** Rinse opened eye for several minutes under running water. Then consult doctor.
- **After swallowing** Seek immediate medical advice.
- **4.2 Most important symptoms and effects, both acute and delayed**
No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

SECTION 5: Firefighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents**
CO₂, extinguishing powder or water jet. Fight larger fires with water jet or alcohol-resistant foam.
- **5.2 Special hazards arising from the substance or mixture**
No further relevant information available.
- **5.3 Advice for firefighters**
- **Protective equipment:** No special measures required.

SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
- **6.2 Environmental precautions:** Dilute with much water.
- **6.3 Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

(Contd. on page 3)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 15.07.2021

Version number 9 (replaces version 8)

Revision: 15.07.2021

Trade name: AMOTHERM WOOD 450 SB - A

(Contd. of page 2)

Ensure adequate ventilation.

6.4 Reference to other sections

See Section 7 for information on safe handling

See Section 8 for information on personal protection equipment.

See Section 13 for information on disposal.

SECTION 7: Handling and storage**7.1 Precautions for safe handling**

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

7.2 Conditions for safe storage, including any incompatibilities**Storage****Requirements to be met by storerooms and containers:**

Store in well closed containers in a cool, well ventilated area. Direct sunshine should be avoided.

Information about storage in one common storage facility: Not required.**Further information about storage conditions:** Keep container tightly sealed.**Storage class** 3**7.3 Specific end use(s)** No further relevant information available.**SECTION 8: Exposure controls/personal protection****8.1 Control parameters****Components with limit values that require monitoring at the workplace:****123-86-4 n-butyl acetate**WEL Short-term value: 966 mg/m³, 200 ppmLong-term value: 724 mg/m³, 150 ppm**108-65-6 2-methoxy-1-methylethyl acetate**WEL Short-term value: 548 mg/m³, 100 ppmLong-term value: 274 mg/m³, 50 ppm

Sk

141-78-6 ethyl acetateWEL Short-term value: 1468 mg/m³, 400 ppmLong-term value: 734 mg/m³, 200 ppm**DNELs****123-86-4 n-butyl acetate**

Oral Long-term exposure, systemic effects 2 mg/kg bw/day (Ver)

Acute, systemic effects 2 mg/kg/day (Ver)

Dermal Long-term exposure, systemic effects 11 mg/kg bw/day (Arb)

6 mg/kg bw/day (Ver)

Acute, local effects 11 mg/kg (Arb)

Acute, systemic effects 6 mg/kg/day (Ver)

Inhalative Long-term exposure, systemic effects 300 mg/m³ (Arb)35.7 mg/m³ (Ver)Long-term exposure, local effects 600 mg/m³ (Arb)35.7 mg/m³ (Ver)Acute, systemic effects 300 mg/m³ (Arb)300 mg/m³ (Ver)Acute, local effects 600 mg/m³ (Arb)300 mg/m³ (Ver)**108-65-6 2-methoxy-1-methylethyl acetate**

Oral Long-term exposure, systemic effects 36 mg/kg bw/day (Ver)

Dermal Long-term exposure, systemic effects 796 mg/kg bw/day (Arb)

320 mg/kg bw/day (Ver)

(Contd. on page 4)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 15.07.2021

Version number 9 (replaces version 8)

Revision: 15.07.2021

Trade name: **AMOTHERM WOOD 450 SB - A**

(Contd. of page 3)

Inhalative	Long-term exposure, systemic effects	275 mg/m ³ (Arb)
		33 mg/m ³ (Ver)
	Long-term exposure, local effects	33 mg/m ³ (Ver)
	Acute, local effects	550 mg/m ³ (Arb)

· PNECs

123-86-4 n-butyl acetate

PNEC	0.18 mg/l (freshwater)
	0.018 mg/l (Marine Water)
	35.6 mg/l (sewage treatment plant microorganisms)
	0.36 mg/l (sporadic release)
PNEC	0.0903 mg/kg (soil)
	0.981 mg/kg (sediment, freshwater)
	0.0981 mg/kg (sediment, marine water)

108-65-6 2-methoxy-1-methylethyl acetate

PNEC	0.635 mg/l (freshwater)
	0.0635 mg/l (Marine Water)
	100 mg/l (sewage treatment plant microorganisms)
PNEC	0.29 mg/kg (soil)
	3.29 mg/kg (sediment, freshwater)
	0.329 mg/kg (sediment, marine water)

· **Additional information:** The lists that were valid during the compilation were used as basis.

· 8.2 Exposure controls

· **Appropriate engineering controls** No further data; see item 7.

· **Individual protection measures, such as personal protective equipment**

· **General protective and hygienic measures**

Wash hands during breaks and at the end of the work.

· **Breathing equipment:**

Filter type A (gas and organic vapours - boiling point >65°C)

Use breathing protection in case of insufficient ventilation.

· **Hand protection**

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves**

Fluorocarbon rubber (Viton)

Rubber gloves

Chloroprene rubber, CR

PVC gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye/face protection**

Gauze goggles

Tightly sealed safety glasses.

· **Body protection:** Light weight protective clothing

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· **General Information**

· **Physical state**

Fluid

· **Colour:**

Whitish

(Contd. on page 5)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 15.07.2021

Version number 9 (replaces version 8)

Revision: 15.07.2021

Trade name: AMOTHERM WOOD 450 SB - A

(Contd. of page 4)

· Odour:	Solvent-like
· Odour threshold:	Not determined.
· Melting point/freezing point:	Not determined
· Boiling point or initial boiling point and boiling range	126 °C (123-86-4 n-butyl acetate)
· Flammability	Not applicable.
· Lower and upper explosion limit	
· Lower:	1.2 Vol % (123-86-4 n-butyl acetate)
· Upper:	7.5 Vol % (123-86-4 n-butyl acetate)
· Flash point:	27 °C (123-86-4 n-butyl acetate)
· Self-inflammability:	Product is not selfigniting.
· Decomposition temperature:	Not determined.
· pH	Mixture is non-polar/aprotic.
· Viscosity:	
· Kinematic viscosity	Not determined.
· dynamic:	Not determined.
· Solubility	
· Water:	Fully miscible
· Partition coefficient n-octanol/water (log value)	Not determined.
· Vapour pressure at 20 °C:	15 hPa (123-86-4 n-butyl acetate)
· Density and/or relative density	
· Density at 20 °C	1.128 g/cm ³
· Relative density	Not determined.
· Vapour density	Not determined.
· 9.2 Other information	
· Appearance:	
· Form:	Fluid
· Important information on protection of health and environment, and on safety.	
· Ignition temperature:	415 °C
· Explosive properties:	Product is not explosive. However, formation of explosive air/steam mixtures is possible.
· Solvent content:	
· Organic solvents:	27.6 %
· VOC (EU)	302.5 g/l
· Solids content:	72.4 %
· Change in condition	
· Evaporation rate	Not determined.
· Information with regard to physical hazard classes	
· Explosives	Void
· Flammable gases	Void
· Aerosols	Void
· Oxidising gases	Void
· Gases under pressure	Void
· Flammable liquids	Flammable liquid and vapour.
· Flammable solids	Void
· Self-reactive substances and mixtures	Void
· Pyrophoric liquids	Void
· Pyrophoric solids	Void
· Self-heating substances and mixtures	Void
· Substances and mixtures, which emit flammable gases in contact with water	Void
· Oxidising liquids	Void
· Oxidising solids	Void
· Organic peroxides	Void
· Corrosive to metals	Void
· Desensitised explosives	Void

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.

(Contd. on page 6)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 15.07.2021

Version number 9 (replaces version 8)

Revision: 15.07.2021

Trade name: AMOTHERM WOOD 450 SB - A

(Contd. of page 5)

- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:**
No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known

SECTION 11: Toxicological information

- **11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**

- **Acute toxicity**

- **LD/LC50 values that are relevant for classification:**

123-86-4 n-butyl acetate

Oral	LD50	10,760 mg/kg (rat)
Dermal	LD50	>14,000 mg/kg (rab)
Inhalative	LC50/4 h	>23.4 mg/l (rat) (OECD 403 Acute Inhalation Toxicity)

13674-84-5 Tris (2-chlorometyletil)phosphate

Oral	LD50	500 mg/kg (ATE)
------	------	-----------------

108-65-6 2-methoxy-1-methylethyl acetate

Oral	LD50	>5,000 mg/kg (rat)
Dermal	LD50	>5,000 mg/kg (rabbit)
Inhalative	LC50/4 h	37.5 mg/l (rat)

- **11.2 Information on other hazards**

- **Endocrine disrupting properties**

78-93-3 butanone

List II

SECTION 12: Ecological information

- **12.1 Toxicity**

- **Aquatic toxicity:**

123-86-4 n-butyl acetate

LC50 96 h	18 mg/l (fish)
LC50 21 d	43.5 mg/l (aquatic invertebrates)
LOEC 21 d	47.6 mg/l (aquatic invertebrates)
EC50 48 h	44 mg/l (aquatic invertebrates)
EC50 72h	246 mg/l (Alga)
EC50 96 h	18 mg/l (fish)
EC50 21 d	34.2 mg/l (aquatic invertebrates)
ErC50 48 h	392 mg/l (Alga)
ErC50 24 h	335 mg/l (Alga)
NOEC 21 d	23.2 mg/l (aquatic invertebrates)
NOEC 48 h	196 mg/l (Alga)
NOEC 24 h	196 mg/l (Alga)

108-65-6 2-methoxy-1-methylethyl acetate

LC50 96 h	180 mg/l (fish)
LC50 14 d	63.5 mg/l (fish)
LOEC 96 h	>1,000 mg/l (Alga)
EC50 48 h	>500 mg/l (aquatic invertebrates)
EC50 21 d	>100 mg/l (aquatic invertebrates)
ErC50 96 h	>1,000 mg/l (Alga)
Wachstum (EbCx) 10% 30 min	>1,000 mg/l (Microorganisms)
NOEC 96 h	100 mg/l (fish)
NOEC 14 d	47.5 mg/l (fish)

- **12.2 Persistence and degradability** No further relevant information available.

(Contd. on page 7)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 15.07.2021

Version number 9 (replaces version 8)

Revision: 15.07.2021

Trade name: AMOTHERM WOOD 450 SB - A

(Contd. of page 6)

- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **12.5 Results of PBT and vPvB assessment**
 - **PBT:** Not applicable.
 - **vPvB:** Not applicable.
- **12.6 Endocrine disrupting properties**
For information on endocrine disrupting properties see section 11.
- **12.7 Other adverse effects**
- **Additional ecological information:**
- **General notes:**
Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water.
Do not allow undiluted product or large quantities of it to reach ground water, water bodies or sewage system.

SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**
- **Recommendation**
Must be specially treated under adherence to official regulations.
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.
- **Recommended cleaning agent:** Water, if necessary with cleaning agent.

SECTION 14: Transport information

- | | |
|---|-----------------------------|
| · 14.1 UN number or ID number | |
| · ADR, IMDG, IATA | UN1263 |
| · 14.2 UN proper shipping name | |
| · ADR | 1263 PAINT |
| · IMDG, IATA | PAINT |
| · 14.3 Transport hazard class(es) | |
| · ADR | |
|  | |
| · Class | 3 (F1) Flammable liquids. |
| · Label | 3 |
| · IMDG, IATA | |
|  | |
| · Class | 3 Flammable liquids. |
| · Label | 3 |
| · 14.4 Packing group | |
| · ADR, IMDG, IATA | III |
| · 14.5 Environmental hazards: | Not applicable. |
| · 14.6 Special precautions for user | Warning: Flammable liquids. |
| · Kemler Number: | 30 |
| · EMS Number: | F-E, S-E |
| · Stowage Category | A |
| · 14.7 Maritime transport in bulk according to IMO instruments | Not applicable. |

(Contd. on page 8)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 15.07.2021

Version number 9 (replaces version 8)

Revision: 15.07.2021

Trade name: AMOTHERM WOOD 450 SB - A

(Contd. of page 7)

· Transport/Additional information:

· ADR

· Limited quantities (LQ)

5L

· Excepted quantities (EQ)

Code: E1

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 1000 ml

· Transport category

3

· Tunnel restriction code

D/E

· IMDG

· Limited quantities (LQ)

5L

· Excepted quantities (EQ)

Code: E1

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 1000 ml

· UN "Model Regulation":

UN 1263 PAINT, 3, III

SECTION 15: Regulatory information

· 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

· Labelling according to Regulation (EC) No 1272/2008 GHS label elements

· Directive 2012/18/EU

· Named dangerous substances - ANNEX I None of the ingredients is listed.

· Seveso category P5c FLAMMABLE LIQUIDS

· Qualifying quantity (tonnes) for the application of lower-tier requirements 5.000 t

· Qualifying quantity (tonnes) for the application of upper-tier requirements 50.000 t

· National regulations

The product is subject to classification in accordance with the prevailing version of the regulations on hazardous materials.

· Technical instructions (air):

Class	Share in %
NK	23.0

· Water hazard class: Water hazard class 1 (Self-assessment): slightly hazardous for water.

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has been carried out.

SECTION 16: Other information

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H226 Flammable liquid and vapour.

H302 Harmful if swallowed.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H336 May cause drowsiness or dizziness.

EUH066 Repeated exposure may cause skin dryness or cracking.

· Department issuing data specification sheet: Environment protection department.

· Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

DNEL: Derived No-Effect Level (REACH)

PNEL: Predicted No-Effect Concentration (REACH)

LC50: Lethal concentration, 50 percent

(Contd. on page 9)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 15.07.2021

Version number 9 (replaces version 8)

Revision: 15.07.2021

Trade name: AMOTHERM WOOD 450 SB - A

(Contd. of page 8)

LD50: Lethal dose, 50 percent
 PBT: Persistent, Bioaccumulative and Toxic
 vPvB: very Persistent and very Bioaccumulative
 Flam. Liq. 3: Flammable liquids – Category 3
 Acute Tox. 4: Acute toxicity – Category 4
 Skin Irrit. 2: Skin corrosion/irritation – Category 2
 Skin Sens. 1: Skin sensitisation – Category 1
 STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
 * **Data compared to the previous version altered.**

Annex: Exposure scenario

- **Short title of the exposure scenario**
- **Sector of Use**
 - SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
 - SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites
- **Product category** PC9a Coatings and paints, thinners, paint removers
- **Process category**
 - PROC11 Non industrial spraying
 - PROC10 Roller application or brushing
 - PROC7 Industrial spraying
- **Description of the activities / processes covered in the Exposure Scenario**
 See section 1 of the annex to the Safety Data Sheet.
- **Conditions of use**
- **Duration and frequency** 5 workdays/week.
- **Physical parameters**
- **Physical state** Fluid
- **Concentration of the substance in the mixture** The substance is main component.
- **Other operational conditions**
- **Other operational conditions affecting environmental exposure**
 Dilute with much water.
 Use only on hard ground.
- **Other operational conditions affecting worker exposure**
 Avoid contact with eyes.
 Avoid contact with the skin.
 Avoid long-term or repeated skin contact.
 Do not breathe gas/vapour/aerosol.
 Take precautionary measures against static discharge.
 Keep away from sources of ignition - No smoking.
- **Other operational conditions affecting consumer exposure** No special measures required.
- **Other operational conditions affecting consumer exposure during the use of the product**
 Not applicable.
- **Risk management measures**
- **Worker protection**
- **Organisational protective measures** No special measures required.
- **Technical protective measures**
 Provide explosion-proof electrical equipment.
 Ensure that suitable extractors are available on processing machines
 Use product only in enclosed systems.
- **Personal protective measures**
 Do not inhale gases / fumes / aerosols.
 Avoid contact with the skin.
 Avoid contact with the eyes.
 Tightly sealed safety glasses.
 Filter type A (gas and organic vapours - boiling point >65°C)
 Use breathing protection in case of insufficient ventilation.
 The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
 Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.
 Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation
- **Measures for consumer protection** Ensure adequate labelling.
- **Environmental protection measures**
- **Water**
 No special measures required.

(Contd. on page 10)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 15.07.2021

Version number 9 (replaces version 8)

Revision: 15.07.2021

Trade name: AMOTHERM WOOD 450 SB - A

(Contd. of page 9)

- Do not allow to reach sewage system.*
- **Soil** Prevent contamination of soil.
- **Disposal measures** Ensure that waste is collected and contained.
- **Disposal procedures**
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Waste type** Partially emptied and uncleaned packaging
- **Exposure estimation**
- **Consumer** Not relevant for this Exposure Scenario.
- **Guidance for downstream users** No further relevant information available.

GB