Safety Data Sheet

According to Annex II to REACH - Regulation 2015/830

SECTION 1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Code:	YO-10C762/--NTR
Product name	CONVERTER/TOP COAT, NEUTRAL

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use	CONVERTER

1.3. Details of the supplier of the safety data sheet

Name	RENNER ITALIA S.P.A.
Full address	Via Ronchi Inferiore, 34
District and Country	40061 Minerbio (BO) Italia
	Tel. +39 051-6618211
	Fax +39 051-6606312
e-mail address of the competent person responsible for the Safety Data Sheet	sds@renneritalia.com

1.4. Emergency telephone number

For urgent inquiries refer to	RENNER ITALIA S.p.A. - Tel. +39 051-6618211 (dal lunedì al venerdì dalle 8.30 - 13.00 e dalle 14.00 - 17.30) ITALIA Centro antiveleni Milano - Tel. +39 02-66101029 Centro antiveleni Firenze - Tel. +39 055-7947819 CROATIA Služba za izvanredna stanja (112) Centar za kontrolu otrovanja (01/2348-342) HUNGARY Egészségügyi Toxikológiai Tájékoztató Szolgálat (ETTSZ) 1096 Budapest, Nagyvárad tér 2. Telefon: +36 1 476 6464 (8-16 óráig), +36 80 201 199 (éjjel-nappal hívható) magyar nyelven LATVIA Valsts ugunsdzesibas un glabšanas dienests: (+371) 112 Saindešanas un zalu informacijas centrs: (+371) 67042473 (visu diennakti) LITHUANIA Apsinuodijimų kontrolės ir Informacijos biuras visą parą tel. (8 5) 236 2052 Bendras pagalbos telefonas: 112 NORWAY Emergency number: 113 POLSKA Numer telefonu alarmowego: +48 22 615 27 51 PORTUGAL Centro de Informação Anti-Venenos: +351 808 250 143 BULGARIA - България Национален център по токсикология, МБАЛСМ “Пирогов” телефон: +359 2 9154 233

SECTION 2. Hazards identification

2.1. Classification of the substance or mixture

The product is not classified as hazardous pursuant to the provisions set forth in EC Regulation 1272/2008 (CLP).
However, since the product contains hazardous substances in concentrations such as to be declared in section no. 3, it requires a safety data sheet with appropriate information, compliant to (EU) Regulation 2015/830.

Hazard classification and indication: --

SECTION 2. Hazards identification ... / >>

2.2. Label elements

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

Hazard pictograms: --

Signal words: --

Hazard statements:

EUH210 Safety data sheet available on request.

EUH208 Contains: 2-METHYL-4-ISOTHIAZOLIN-3-ONE
Mixture of: 5-chloro-2-methyl-2h-isothiazol-3-one and 2-methyl-2h-isothiazol-3-one
methyl- 2H- isothiazol- 3-one (3:1)
May produce an allergic reaction.

Precautionary statements: --

2.3. Other hazards

On the basis of available data, the product does not contain any PBT or vPvB in percentage ≥ than 0,1%.

SECTION 3. Composition/information on ingredients

3.2. Mixtures

Contains:

Identification	x = Conc. %	Classification 1272/2008 (CLP)
2-BUTOXYETHANOL		
CAS 111-76-2	1 ≤ x < 2	Acute Tox. 4 H302, Acute Tox. 4 H312, Acute Tox. 4 H332, Eye Irrit. 2 H319, Skin Irrit. 2 H315
EC 203-905-0		
INDEX 603-014-00-0		
Reg. no. 01-2119475108-36-xxxx		
Mixture of: 5-chloro-2-methyl-2h-isothiazol-3-one and 2-methyl-2h-isothiazol-3-one methyl- 2H- isothiazol- 3-one (3:1)		
CAS 55965-84-9	0 ≤ x < 0,0015	Acute Tox. 2 H310, Acute Tox. 2 H330, Acute Tox. 3 H301, Skin Corr. 1B H314, Eye Dam. 1 H318, Skin Sens. 1 H317, Aquatic Acute 1 H400 M=100, Aquatic Chronic 1 H410 M=10
EC		
INDEX 613-167-00-5		
Reg. no. 01-2120764691-48-xxxx		
2-METHYL-4-ISOTHIAZOLIN-3-ONE		
CAS 2682-20-4	0 ≤ x < 0,0015	Acute Tox. 2 H330, Acute Tox. 3 H301, Acute Tox. 3 H311, Skin Corr. 1C H314, Eye Dam. 1 H318, Skin Sens. 1A H317, Aquatic Acute 1 H400 M=10, Aquatic Chronic 1 H410 M=1
EC 220-239-6		
INDEX 613-167-00-5		
Reg. no.		

The full wording of hazard (H) phrases is given in section 16 of the sheet.

SECTION 4. First aid measures

4.1. Description of first aid measures

EYES: Remove contact lenses, if present. Wash immediately with plenty of water for at least 30-60 minutes, opening the eyelids fully. Get medical advice/attention.
SKIN: Remove contaminated clothing. Rinse skin with a shower immediately. Get medical advice/attention.
INGESTION: Have the subject drink as much water as possible. Get medical advice/attention. Do not induce vomiting unless explicitly authorised by a doctor.
INHALATION: Get medical advice/attention immediately. Remove victim to fresh air, away from the accident scene. If the subject stops breathing, administer artificial respiration. Take suitable precautions for rescue workers.

SECTION 4. First aid measures ... / >>

4.2. Most important symptoms and effects, both acute and delayed

Specific information on symptoms and effects caused by the product are unknown.

4.3. Indication of any immediate medical attention and special treatment needed

Information not available

SECTION 5. Firefighting measures

5.1. Extinguishing media

SUITABLE EXTINGUISHING EQUIPMENT
The extinguishing equipment should be of the conventional kind: carbon dioxide, foam, powder and water spray.
UNSUITABLE EXTINGUISHING EQUIPMENT
None in particular.

5.2. Special hazards arising from the substance or mixture

HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE
Do not breathe combustion products.

5.3. Advice for firefighters

GENERAL INFORMATION
Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.
SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS
Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

SECTION 6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Block the leakage if there is no hazard.
Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

6.2. Environmental precautions

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

6.3. Methods and material for containment and cleaning up

Collect the leaked product into a suitable container. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material.
Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

6.4. Reference to other sections

Any information on personal protection and disposal is given in sections 8 and 13.

SECTION 7. Handling and storage

7.1. Precautions for safe handling

Before handling the product, consult all the other sections of this material safety data sheet. Avoid leakage of the product into the environment. Do not eat, drink or smoke during use. Remove any contaminated clothes and personal protective equipment before entering places in which people eat.

7.2. Conditions for safe storage, including any incompatibilities

Store only in the original container. Store the containers sealed, in a well ventilated place, away from direct sunlight. Keep containers away from any incompatible materials, see section 10 for details.

SECTION 7. Handling and storage ... / >>

7.3. Specific end use(s)

Information not available

SECTION 8. Exposure controls/personal protection

8.1. Control parameters

Regulatory References:

BGR	България	МИНИСТЕРСТВО НА ТРУДА И СОЦИАЛНАТА ПОЛИТИКА МИНИСТЕРСТВО НА ЗДРАВЕОПАЗВАНЕТО НАРЕДБА No 13 от 30 декември 2003 г (4 Септември 2018г)
CZE	Česká Republika	Nařízení vlády č. 246/2018 Sb. Nařízení vlády, kterým se mění nařízení vlády č. 361/2007 Sb., kterým se stanoví podmínky ochrany zdraví při práci, ve znění pozdějších předpisů
DEU	Deutschland	TRGS 900 - Seite 1 von 69 (Fassung 29.03.2019)- Liste der Arbeitsplatzgrenzwerte und Kurzzeitwerte
ESP	España	LÍMITES DE EXPOSICIÓN PROFESIONAL PARA AGENTES QUÍMICOS EN ESPAÑA 2019 (INSST)
EST	Eesti	Ohtlike kemikaalide ja neid sisaldavate materjalide kasutamise töötervishoiu ja tööohutuse nõuded ning töökeskkonna keemiliste ohutegurite piirnormid [RT I, 17.10.2019, 1 - jõust. 17.01.2020]
FRA	France	Valeurs limites d'exposition professionnelle aux agents chimiques en France. ED 984 - INRS
GRC	Ελλάδα	ΕΦΗΜΕΡΙΔΑ ΤΗΣ ΚΥΒΕΡΝΗΣΕΩΣ - ΤΕΥΧΟΣ ΠΡΩΤΟ Αρ. Φύλλου 152 - 21 Αυγούστου 2018
HUN	Magyarország	A pénzügyminiszter 7/2018. (VIII. 29.) PM rendelete a munkahelyek kémiai biztonságáról szóló 25/2000. (IX. 30.) EüM–SZCSM együ, TTes rendelet módosításáról.
HRV	Hrvatska	Pravilnik o zaštiti radnika od izloženosti opasnim kemikalijama na radu, graničnim vrijednostima izloženosti i biološkim graničnim vrijednostima (NN 91/18)
ITA	Italia	Decreto Legislativo 9 Aprile 2008, n.81
LTU	Lietuva	LIETUVOS HIGIENOS NORMA HN 23:2011 „CHEMINIŲ MEDŽIAGŲ PROFESINIO POVEIKIO RIBINIAI DYDŽIAI. MATAVIMO IR POVEIKIO VERTINIMO BENDRIEJI REIKALAVIMAI. Nr. V-695/A1-272, 2018-06-12, paskelbta TAR 2018-06-15, i. k. 2018-09988
LVA	Latvija	Ķīmisko vielu aroda ekspozīcijas robežvērtības (AER) darba vides gaisā 2018
NOR	Norge	Fastsatt av Arbeids- og sosialdepartementet 21. august 2018 med hjemmel i lov 17. juni 2005 nr. 62 om arbeidsmiljø, arbeidstid, stillingsvern mv. (arbeidsmiljøloven) § 1-3, § 1-4 og § 4-5
NLD	Nederland	Regeling van de Staatssecretaris van Sociale Zaken en Werkgelegenheid van 13 juli 2018, 2018-0000118517 tot wijziging van de Arbeidsomstandighedenregeling in verband met de implementatie van Richtlijn 2017/164 in Bijlage XIII
PRT	Portugal	Ministério da Economia e do Emprego Consolida as prescrições mínimas em matéria de protecção dos trabalhadores contra os riscos para a segurança e a saúde devido à exposição a agentes químicos no trabalho - Diário da República, 1.ª série - N.º 111 - 11 de junho de 2018
POL	Polska	ROZPORZĄDZENIE MINISTRA RODZINY, PRACY I POLITYKI SPOŁECZNEJ z dnia 12 czerwca 2018 r
ROU	România	HOTĂRÂRE nr. 584 din 2 august 2018 pentru modificarea Hotărârii Guvernului nr. 1.218/2006 privind stabilirea cerințelor minime de securitate și sănătate în muncă pentru asigurarea protecției lucrătorilor împotriva riscurilor legate de prezența agenților chimici
SVK	Slovensko	Nariadenie vlády č. 33/2018 Z. z. Nariadenie vlády Slovenskej republiky, ktorým sa mení a dopĺňa nariadenie vlády Slovenskej republiky č. 355/2006 Z. z. o ochrane zamestnancov pred rizikami súvisiacimi s expozíciou chemickým faktorom pri práci v znení neskorších predpisov
SVN	Slovenija	Uradni list Republike Slovenije 20.12.2019 - Uradnem listu RS št. 78/19 -PRAVILNIK o varovanju delavcev pred tveganji zaradi izpostavljenosti kemičnim snovem pri delu
TUR	Türkiye	23.06.2017 tarihli, 30105 sayılı, KKDİK Ek II Yönetmelik hükümlerine uygun düzenlenmiştir
GBR	United Kingdom	EH40/2005 Workplace exposure limits (Third edition, published 2018)
EU	OEL EU	Directive (EU) 2019/1831; Directive (EU) 2019/130; Directive (EU) 2019/983; Directive (EU) 2017/2398; Directive (EU) 2017/164; Directive 2009/161/EU; Directive 2006/15/EC; Directive 2004/37/EC; Directive 2000/39/EC; Directive 98/24/EC; Directive 91/322/EEC.
	TLV-ACGIH	ACGIH 2020

SECTION 8. Exposure controls/personal protection ... / >>

2-BUTOXYETHANOL

Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations	
		mg/m3	ppm	mg/m3	ppm		
TLV	BGR	98	20	246	50	SKIN	
TLV	CZE	100	20,4	200	40,8	SKIN	
AGW	DEU	49	10	98 (C)	20 (C)	SKIN	
MAK	DEU	49	10	98	20	SKIN	Hinweis
VLA	ESP	98	20	245	50	SKIN	
TLV	EST	98	20	246	50		
VLEP	FRA	49	10	246	50	SKIN	
TLV	GRC	120	25				
AK	HUN	98		246		SKIN	
GVI/KGVI	HRV	98	20	246	50	SKIN	
VLEP	ITA	98	20	246	50	SKIN	
RD	LTU	50	10	100	20	SKIN	
RV	LVA	98	20	246	50	SKIN	
TLV	NOR	50	10			SKIN	
TGG	NLD	100		246		SKIN	
VLE	PRT	98	20	246	50	SKIN	
NDS/NDSCh	POL	98		200		SKIN	
TLV	ROU	98	20	246	50	SKIN	
NPEL	SVK	98	20	246	50	SKIN	
MV	SVN	98	20	246	50	SKIN	
ESD	TUR	98	20	246	50	SKIN	
WEL	GBR	123	25	246	50	SKIN	
OEL	EU	98	20	246	50	SKIN	
TLV-ACGIH		97	20				

Predicted no-effect concentration - PNEC

Normal value in fresh water	8,8	mg/l
Normal value in marine water	0,88	mg/l
Normal value for fresh water sediment	34,6	mg/kg
Normal value for marine water sediment	3,46	mg/kg
Normal value for water, intermittent release	9,1	mg/l
Normal value of STP microorganisms	463	mg/l
Normal value for the food chain (secondary poisoning)	20	mg/kg
Normal value for the terrestrial compartment	2,33	mg/kg

Health - Derived no-effect level - DNEL / DMEL

	Effects on consumers				Effects on workers			
Route of exposure	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral	VND	26,7 mg/kg/d	VND	6,3 mg/kg/d				
Inhalation	426 mg/m3	147 mg/m3	VND	59 mg/m3	246 mg/m3	1091 mg/m3	VND	98 mg/m3
Skin	VND	89 mg/kg/d	VND	75 mg/kg/d	VND	89 mg/kg/d	VND	125 mg/kg/d

Mixture of: 5-chloro-2-methyl-2h-isothiazol-3-one and 2-methyl-2h-isothiazol-3-one

SECTION 8. Exposure controls/personal protection ... / >>

methyl- 2H- isothiazol- 3-one (3:1)

Threshold Limit Value						
Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
AGW	DEU	0,2				INHAL
MV	SVN	0,05				

Predicted no-effect concentration - PNEC		
Normal value in fresh water	0,00339	mg/l
Normal value in marine water	0,00339	mg/l
Normal value for water, intermittent release	0,00339	mg/l
Normal value of STP microorganisms	0,23	mg/l

Health - Derived no-effect level - DNEL / DMEL								
	Effects on consumers				Effects on workers			
Route of exposure	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral		0,11 mg/kg bw/d		0,09 mg/kg bw/d				
Inhalation	0,02 mg/m3		0,04 mg/m3		0,04 mg/m3		0,02 mg/m3	

2-METHYL-4-ISOTHIAZOLIN-3-ONE

Threshold Limit Value						
Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
MAK	DEU	0,2				INHAL
MV	SVN	0,05				

CALCIUM CARBONATE

Threshold Limit Value						
Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
VLA	ESP	10				
NDS/NDSCh	POL	10				
WEL	GBR	4				

Legend:
(C) = CEILING ; INHAL = Inhalable Fraction ; RESP = Respirable Fraction ; THORA = Thoracic Fraction.
VND = hazard identified but no DNEL/PNEC available ; NEA = no exposure expected ; NPI = no hazard identified.

8.2. Exposure controls

Take the normal precautions for handling chemicals and apply an adequate standard of workplace hygiene.
Users must assess the risks in their workplace and adopt:
- Primary collective protective measures such as adequate natural ventilation and local extraction
- Personal protective equipment to manage the combination of residual risks
Personal protective equipment varies according to the possible exposure and hazardousness of the working conditions, so the final choice depends on the risk assessment.

HAND PROTECTION
Use category III chemical resistant gloves according to the EN 374 standard
Brief contact (splash protection) – non-exhaustive list
Suitable material: NITRILE RUBBER (NBR)
Glove thickness: greater than 0.4 mm
Breakthrough time: from 30 to 60 minutes
Breakthrough index: at least 2
The gloves must be replaced if there are signs of deterioration. In any case, users must assess the risks to determine the most suitable type of glove for the conditions of use.

SKIN PROTECTION
Wear work clothes and safety footwear that complies with EN ISO 20344

EYE PROTECTION
Wear safety glasses (EN 166).

RESPIRATORY PROTECTION
Use a mask with EN140 and/or EN136 approval, with an ABEK type filter (EN 14387)

SECTION 8. Exposure controls/personal protection ... / >>

ENVIRONMENTAL EXPOSURE CONTROLS
The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

SECTION 9. Physical and chemical properties

NOTE: Determination of the flash point may be NA (not applicable), the product being non flammable.

9.1. Information on basic physical and chemical properties

Properties	Value	Information
Appearance	liquid	
Colour	white	
Odour	characteristic	
Odour threshold	Not available	
pH	7,0-9,0	
Melting point / freezing point	Not available	
Initial boiling point	100 °C	
Boiling range	Not available	
Flash point	Not applicable	
Evaporation Rate	Not available	
Flammability of solids and gases	not applicable	
Lower inflammability limit	Not available	
Upper inflammability limit	Not available	
Lower explosive limit	Not available	
Upper explosive limit	Not available	
Vapour pressure	Not available	
Vapour density	Not available	
Relative density	1,05	
Solubility	soluble in water	
Partition coefficient: n-octanol/water	Not available	
Auto-ignition temperature	Not available	
Decomposition temperature	Not available	
Viscosity	Not available	
Explosive properties	not applicable	
Oxidising properties	not applicable	

9.2. Other information

Total solids (250°C / 482°F)	29,80 %			
VOC (Directive 2010/75/EC) :	2,02 %	-	21,24	g/litre
VOC (volatile carbon) :	1,21 %	-	12,71	g/litre

SECTION 10. Stability and reactivity

LITHIUM CHLORIDE
LITHIUM CHLORIDE - Avoid moisture exposure. Incompatible materials: strong acids, strong oxidising agents, bromine trifluoride.
In case of fire, it can release: lithium oxides, gassy hydrochloric acid

TRIETHYLENE GLYCOL MONOBUTYL ETHER
TRIETHYLENE GLYCOL MONOBUTYL ETHER: Incompatible materials: strong bases, strong oxidising agents, acids.

10.1. Reactivity

There are no particular risks of reaction with other substances in normal conditions of use.

2-BUTOXYETHANOL
Decomposes under the effect of heat.

10.2. Chemical stability

The product is stable in normal conditions of use and storage.

10.3. Possibility of hazardous reactions

SECTION 10. Stability and reactivity ... / >>

No hazardous reactions are foreseeable in normal conditions of use and storage.

2-BUTOXYETHANOL
May react dangerously with: aluminium,oxidising agents.Forms peroxides with: air.

10.4. Conditions to avoid

None in particular. However the usual precautions used for chemical products should be respected.

2-BUTOXYETHANOL
Avoid exposure to: sources of heat,naked flames.

10.5. Incompatible materials

Information not available

10.6. Hazardous decomposition products

2-BUTOXYETHANOL
May develop: hydrogen.

SECTION 11. Toxicological information

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification.
It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the toxicological effects of exposure to the product.

11.1. Information on toxicological effects

Metabolism, toxicokinetics, mechanism of action and other information

Information not available

Information on likely routes of exposure

ETHYLBENZENE
WORKERS: inhalation; contact with the skin.
POPULATION: ingestion of contaminated food or water; contact with the skin of products containing the substance.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

ETHYLBENZENE
As the counterparts of benzene, may have an acute effect on the central nervous system, with depression, narcosis, often preceded by dizziness and associated with headache (Ispesl). Is irritating for skin, conjunctiva and respiratory tract.

Interactive effects

Information not available

ACUTE TOXICITY

ATE (Inhalation) of the mixture:	> 20 mg/l
ATE (Oral) of the mixture:	>2000 mg/kg
ATE (Dermal) of the mixture:	>2000 mg/kg

2-BUTOXYETHANOL

LD50 (Oral)	1300 mg/kg
LD50 (Dermal)	2000 mg/kg
LC50 (Inhalation)	11 mg/l/4h

Mixture of: 5-chloro-2-methyl-2h-isothiazol-3-one and 2-methyl-2h-isothiazol-3-one
methyl- 2H- isothiazol- 3-one (3:1)

LD50 (Oral)	66 mg/kg
LD50 (Dermal)	141 mg/kg
LC50 (Inhalation)	0,17 mg/l/4h

POLYETHYLENE WAX

LD50 (Oral)	> 2000 mg/kg

SECTION 11. Toxicological information ... / >>

2-METHYL-4-ISOTHIAZOLIN-3-ONE

LD50 (Oral)	183 mg/kg
LD50 (Dermal)	218 mg/kg
LC50 (Inhalation)	0,53 mg/l/4h

CALCIUM CARBONATE

LD50 (Oral)	15000 mg/kg Rat

SKIN CORROSION / IRRITATION

Does not meet the classification criteria for this hazard class

SERIOUS EYE DAMAGE / IRRITATION

Does not meet the classification criteria for this hazard class

RESPIRATORY OR SKIN SENSITISATION

May produce an allergic reaction.
Contains:
2-METHYL-4-ISOTHIAZOLIN-3-ONE
Mixture of: 5-chloro-2-methyl-2h-isothiazol-3-one and 2-methyl-2h-isothiazol-3-one
methyl- 2H- isothiazol- 3-one (3:1)

GERM CELL MUTAGENICITY

Does not meet the classification criteria for this hazard class

CARCINOGENICITY

Does not meet the classification criteria for this hazard class

REPRODUCTIVE TOXICITY

Does not meet the classification criteria for this hazard class

STOT - SINGLE EXPOSURE

Does not meet the classification criteria for this hazard class

STOT - REPEATED EXPOSURE

Does not meet the classification criteria for this hazard class

ASPIRATION HAZARD

Does not meet the classification criteria for this hazard class

SECTION 12. Ecological information

Use this product according to good working practices. Avoid littering. Inform the competent authorities, should the product reach waterways or contaminate soil or vegetation.

12.1. Toxicity

2-BUTOXYETHANOL

LC50 - for Fish	1474 mg/l/96h Oncorhynchus mykiss
EC50 - for Crustacea	1550 mg/l/48h Daphnia magna
EC50 - for Algae / Aquatic Plants	1840 mg/l/72h Pseudokirchneriella subcapitata
Chronic NOEC for Fish	> 100 mg/l Brachydanio rerio
Chronic NOEC for Crustacea	100 mg/l Daphnia magna

Mixture of: 5-chloro-2-methyl-2h-isothiazol-3-one and 2-methyl-2h-isothiazol-3-one
methyl- 2H- isothiazol- 3-one (3:1)

LC50 - for Fish	0,188 mg/l/96h Oncorhynchus mykiss
EC50 - for Crustacea	0,16 mg/l/48h Daphnia magna
EC50 - for Algae / Aquatic Plants	0,0052 mg/l/72h Skeletonema costatum
Chronic NOEC for Fish	0,098 mg/l Oncorhynchus mykiss (28 d)

SECTION 12. Ecological information ... / >>

Chronic NOEC for Crustacea	0,004 mg/l Daphnia magna (21 d)
Chronic NOEC for Algae / Aquatic Plants	0,0012 mg/l Skeletonema costatum

POLYETHYLENE WAX

LC50 - for Fish	> 100 mg/l/96h

2-METHYL-4-ISOTHIAZOLIN-3-ONE

LC50 - for Fish	> 150 mg/l/96h Danio rerio
EC50 - for Crustacea	0,87 mg/l/48h Daphnia magna
EC50 - for Algae / Aquatic Plants	0,157 mg/l/72h Selenastrum capricornutum
Chronic NOEC for Crustacea	0,044 mg/l
Chronic NOEC for Algae / Aquatic Plants	0,0104 mg/l Psudokirchneriella subcapitata

12.2. Persistence and degradability

2-BUTOXYETHANOL

Solubility in water	1000 - 10000 mg/l

Rapidly degradable

Mixture of: 5-chloro-2-methyl-2h-isothiazol-3-one and 2-methyl-2h-isothiazol-3-one
methyl- 2H- isothiazol- 3-one (3:1)
NOT rapidly degradable

2-METHYL-4-ISOTHIAZOLIN-3-ONE
NOT rapidly degradable

12.3. Bioaccumulative potential

2-BUTOXYETHANOL

Partition coefficient: n-octanol/water	0,81

2-METHYL-4-ISOTHIAZOLIN-3-ONE

Partition coefficient: n-octanol/water	-0,32

12.4. Mobility in soil

2-BUTOXYETHANOL

Partition coefficient: soil/water	0,45

12.5. Results of PBT and vPvB assessment

On the basis of available data, the product does not contain any PBT or vPvB in percentage ≥ than 0,1%.

12.6. Other adverse effects

Information not available

SECTION 13. Disposal considerations

13.1. Waste treatment methods

For disposal or recovery in EU countries , use the relevant waste code (EWC code) identified in the European Waste Catalogue. The producer of the waste must assign the EWC code according to the sector and type of process. Disposal must be carried out by an authorised waste management company.
After the producer of the waste has assigned the EWC code, the contaminated packaging must be sent for recovery or disposal in compliance with the European waste management regulations. Disposal must be carried out by an authorised waste management company.
For waste disposal or recovery in countries outside the EU, comply with the national or local regulations in force. For disposal or recovery of contaminated packaging in countries outside the EU, comply with the national or local regulations in force.
Waste transportation may be subject to regulations on transportation of hazardous goods.

SECTION 14. Transport information

The product is not dangerous under current provisions of the Code of International Carriage of Dangerous Goods by Road (ADR) and by Rail (RID), of the International Maritime Dangerous Goods Code (IMDG), and of the International Air Transport Association (IATA) regulations.

14.1. UN number

Not applicable

14.2. UN proper shipping name

Not applicable

14.3. Transport hazard class(es)

Not applicable

14.4. Packing group

Not applicable

14.5. Environmental hazards

Not applicable

14.6. Special precautions for user

Not applicable

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Information not relevant

SECTION 15. Regulatory information

Only for uses exempt from EU DIRECTIVE 2004/42/CE.

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Seveso Category - Directive 2012/18/EC: None

Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006

Product
Point 40

Substances in Candidate List (Art. 59 REACH)
On the basis of available data, the product does not contain any SVHC in percentage ≥ than 0,1%.

Substances subject to authorisation (Annex XIV REACH)
None

Substances subject to exportation reporting pursuant to (EC) Reg. 649/2012:
None

Substances subject to the Rotterdam Convention:
None

Substances subject to the Stockholm Convention:
None

SECTION 15. Regulatory information ... / >>

Healthcare controls
Information not available

15.2. Chemical safety assessment

A chemical safety assessment has not been performed for the preparation/for the substances indicated in section 3.

SECTION 16. Other information

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

Acute Tox. 2	Acute toxicity, category 2
Acute Tox. 3	Acute toxicity, category 3
Acute Tox. 4	Acute toxicity, category 4
Skin Corr. 1B	Skin corrosion, category 1B
Skin Corr. 1C	Skin corrosion, category 1C
Eye Irrit. 2	Eye irritation, category 2
Skin Irrit. 2	Skin irritation, category 2
Skin Sens. 1	Skin sensitization, category 1
Skin Sens. 1A	Skin sensitization, category 1A
Aquatic Acute 1	Hazardous to the aquatic environment, acute toxicity, category 1
Aquatic Chronic 1	Hazardous to the aquatic environment, chronic toxicity, category 1
H310	Fatal in contact with skin.
H330	Fatal if inhaled.
H301	Toxic if swallowed.
H311	Toxic in contact with skin.
H302	Harmful if swallowed.
H312	Harmful in contact with skin.
H332	Harmful if inhaled.
H314	Causes severe skin burns and eye damage.
H319	Causes serious eye irritation.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
EUH210	Safety data sheet available on request.

LEGEND:
- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- CAS NUMBER: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE NUMBER: Identifier in ESIS (European archive of existing substances)
- CLP: EC Regulation 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX NUMBER: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent bioaccumulative and toxic as REACH Regulation
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PNEC: Predicted no effect concentration
- REACH: EC Regulation 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA STEL: Short-term exposure limit
- TWA: Time-weighted average exposure limit
- VOC: Volatile organic Compounds

SECTION 16. Other information ... / >>

- vPvB: Very Persistent and very Bioaccumulative as for REACH Regulation- WGK: Water hazard classes (German).

GENERAL BIBLIOGRAPHY

1. Regulation (EC) 1907/2006 (REACH) of the European Parliament
2. Regulation (EC) 1272/2008 (CLP) of the European Parliament
3. Regulation (EU) 790/2009 (I Atp. CLP) of the European Parliament
4. Regulation (EU) 2015/830 of the European Parliament
5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament
9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
10. Regulation (EU) 2015/1221 (VII Atp. CLP) of the European Parliament
11. Regulation (EU) 2016/918 (VIII Atp. CLP) of the European Parliament
12. Regulation (EU) 2016/1179 (IX Atp. CLP)
13. Regulation (EU) 2017/776 (X Atp. CLP)
14. Regulation (EU) 2018/669 (XI Atp. CLP)
15. Regulation (EU) 2018/1480 (XIII Atp. CLP)
16. Regulation (EU) 2019/521 (XII Atp. CLP)

- The Merck Index. - 10th Edition
- Handling Chemical Safety
- INRS - Fiche Toxicologique (toxicological sheet)
- Patty - Industrial Hygiene and Toxicology
- N.I. Sax - Dangerous properties of Industrial Materials-7, 1989 Edition
- IFA GESTIS website
- ECHA website
- Database of SDS models for chemicals - Ministry of Health and ISS (Istituto Superiore di Sanità) - Italy

Note for users:
The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.
This document must not be regarded as a guarantee on any specific product property.
The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.
Provide appointed staff with adequate training on how to use chemical products.

CALCULATION METHODS FOR CLASSIFICATION
Chemical and physical hazards: Product classification derives from criteria established by the CLP Regulation, Annex I, Part 2. The data for evaluation of chemical-physical properties are reported in section 9.
Health hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 3, unless determined otherwise in Section 11.
Environmental hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 4, unless determined otherwise in Section 12.

Changes to previous review:
The following sections were modified:
03 / 08 / 11 / 12 / 16.